

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)
[First Hit](#)

☐ [Generate Collection](#)

L3: Entry 3 of 7

File: JPAB

Dec 9, 1991

PUB-NO: JP403278071A
DOCUMENT-IDENTIFIER: JP 03278071 A
TITLE: IMAGE RECORDING SYSTEM

PUBN-DATE: December 9, 1991

INVENTOR-INFORMATION:

NAME	COUNTRY
YAMAGUCHI, TAKEO	
KOJIMA, AKIO	
TERAMURA, KAORU	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
RICOH CO LTD	

APPL-NO: JP02126997
APPL-DATE: May 18, 1990

US-CL-CURRENT: 399/176
INT-CL (IPC): G03G 15/00; G03G 15/02; G03G 15/056; G11B 11/12

ABSTRACT:

PURPOSE: To realize a novel transfer system and to reduce the size of the device by heating an optional point of a polymer film subjected to polarization treatment to a temperature of Curie point or more to depolarize it and to form an electrostatic latent image, and developing it with a developing agent.

CONSTITUTION: Ferroelectric polymers are polarized by applying an electric field and hold electric charge on the surface, and an optional point of the polymer film subjected to the polarization treatment is heated to \geq Curie point to depolarize it and to form the electrostatic latent image by utilizing this characteristics. This latent image is developed by the developing agent. As the ferroelectric polymer compound to be used for forming a recording layer, a vinylidene fluoride-vinylidene trifluoride copolymer is most desirable, and this recording operation is carried out by focusing semiconductor laser beams to irradiate an optional point and to raise its temperature to \geq Curie point, and depolarizing it, thus permitting the device to be reduced in the size and weight and image element density to be enhanced, and a single printing plate to be used repeatedly.

COPYRIGHT: (C)1991, JPO&Japio

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)